

FUNCTION

For general construction, framing, sub-flooring, roof sheathing, decks, fences, pallets, boxes, and crates Fits most 15° wire coil framing nailers

FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)

Smooth Shanks provide lower withdrawal strength when compared to ring shanks and spiral shanks

Ring Shanks are deformed to have repeated ridges to increase withdrawal strength

CORROSION

Brite finishes offer little to no corrosion protection

Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards

CAUTION

Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener Electro Galvanized (EG) shall not be used within 3000 feet of saltwater

All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

TECHNICAL	Length x Dia	Penny	Gauge	Head	Deformation	Nails	ASTM F1667			
		Length	(W&M)	Diameter	Length, MIN	per Coil	Bend Yield*			
	2 x .113	6d	11.5	Ø 0.266 in	1.13 in	250	100,000 psi			
	2-1/2 x .131	8d	10.25	Ø 0.266 in	1.25 in	250	100,000 psi			
	2-3/8 x .113	-	11.5	Ø 0.266 in	1.25 in	250	100,000 psi			
	3 x .120	10d	11	Ø 0.281 in	1.50 in	250	100,000 psi			
	3 x .131	10d	10.25	Ø 0.281 in	-	250	100,000 psi			
	3-1/4 x .120	12d	11	Ø 0.281 in	1.50 in	250	100,000 psi			
	3-1/4 x .131	12d	10.25	Ø 0.281 in	-	250	100,000 psi			
* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only										

PRODUCT	Size	Box Count	Brite	EG	HDG	305 SS	316 SS
		QTY	sku	sku	sku	sku	sku
Smooth	2 x .113	3000	0616633	-	-	-	-
Smooth	2-3/8 x .113	3000	0616653	-	0616852	-	-
Smooth	3 x .120	2500	0616673	-	0616870	-	-
Smooth	3 x .120	4000	0616674	-	-	-	-
Smooth	3 x .131	2500	0616670	-	-	-	-
Smooth	3-1/4 x .120	2500	0616690	-	0616890	-	-
Smooth	3-1/4 x .131	2500	0616693	-	-	-	-
Ring	2 x .113	3000	0616433	-	-	-	-
Ring	2-1/2 x .131	4500	-	0616955	-	-	-
Ring	17-3/8 x 113	3000	0616453	-	0634151	-	-
Ring		4500	0616455	0616455EG	-	-	-
Ring	3 x .120	2500	0616473	-	0634171	-	-
Ring	3-1/4 x .120	2500	-	-	0634181	-	-
N015S2005	Page 1 of 1						evised 5.29.2025