

JOB NAME:

CONTRACTOR:

DATE:

STINGER®



PLASTIC CAP & NAIL

TYPE

Ring



FUNCTION

Hand driven fastener
For indoor or outdoor applications
Designed for installation of synthetic underlayment, roofing felt, housewrap, and insulation

FEATURES

Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength
Pre-assembled nail to plastic cap

CORROSION

Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance
Cap is formed using a polymer compatible with the injection-molding process

CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
Electro Galvanized (EG) shall not be used within 3000 feet of saltwater
All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

TECHNICAL	Cap	Cap			Nail	Nail	ASTM F1667
	Diameter	Edge Lip			Length	Shank	Bend Yield*
	1 in ±.063	0.035 in			up to 3 in	Ø 0.105 in	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

PRODUCT	Length Nail	Penny Length	Box Count QTY	EG sku	HDG sku	304 SS sku	316 SS sku
Box	3/4 in	-	2000	0135033	-	-	-
Box	7/8 in	-	2000	0135043	-	-	-
Box	1 in	2d	2000	0135053	-	-	-
Box	1-1/4 in	3d	2000	0135073	-	-	-
Box	1-1/2 in	4d	2000	0135093	-	-	-
Box	1-3/4 in	5d	2000	0135113	-	-	-
Box	2 in	6d	2000	0135133	-	-	-
Box	2-1/2 in	8d	2000	0135153	-	-	-
Box	3 in	10d	2000	0135173	-	-	-
Pail	3/4 in	-	3000	0135031	-	-	-
Pail	7/8 in	-	3000	0135041	-	-	-
Pail	1 in	2d	3000	0135051	-	-	-
Pail	1-1/4 in	3d	2500	0135071	-	-	-
Pail	1-1/2 in	4d	2000	0135091	-	-	-
Pail	1-3/4 in	5d	2000	0135111	-	-	-
Pail	2 in	6d	2000	0135131	-	-	-
Pail	2-1/2 in	8d	2000	0135151	-	-	-
Pail	3 in	10d	-	-	-	-	-