


JOB NAME:

CONTRACTOR:

DATE:

STINGER



WIRE COIL COLLATION FOR ROOFING NAILS

TYPES

Smooth



Ring



FUNCTION

For applying roofing asphalt shingles, insulation board, and felt to wood substructures
Fits most 15° wire coil roofing nailers

FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
Smooth Shanks provide lower withdrawal strength when compared to ring shanks
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength

CORROSION

Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance
Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards
300-series Stainless Steel is suitable for all marine applications

CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
Electro Galvanized (EG) shall not be used within 3000 feet of saltwater
Only 300-series Stainless Steel will prevent tannin staining when used with cedar, cement board, or redwood
All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

TECHNICAL	Length x Dia	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	Nails per Coil	ASTM F1667 Bend Yield*
	3/4 x .120	-	11	Ø .375 in	full length	200	100,000 psi
	7/8 x .120	-	11	Ø .375 in	full length	200	100,000 psi
	1 x .120	2d	11	Ø .375 in	full length	200	100,000 psi
	1-1/4 x .120	3d	11	Ø .375 in	1.00 in	200	100,000 psi
	1-1/2 x .120	4d	11	Ø .375 in	1.00 in	200	100,000 psi
	1-3/4 x .120	5d	11	Ø .375 in	1.00 in	200	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

PRODUCT	Length x Dia	Box Count QTY	Brite sku	EG sku	HDG sku	305 SS sku	316 SS sku
Smooth	3/4 x .120	7200	-	0611030	-	-	-
Smooth	7/8 x .120	7200	-	0611040	-	-	-
Smooth	1 x .120	7200	-	0611050	-	-	-
Smooth	1-1/4 x .120	7200	-	0611070	0611073	-	-
Smooth	1-1/2 x .120	7200	-	0611090	-	-	-
Smooth	1-3/4 x .120	7200	-	0061110	-	-	-
Ring	1-1/4 x .120	3600	-	-	-	0611074	-
Ring	1-1/4 x .120	7200	-	-	0611075	-	-
Ring	1-1/2 x .120	3600	-	0611072	-	0611094	-
Ring	1-3/4 x .120	3600	-	-	-	0611114	-